Pedestrian / Warning Signs

- MUTCD Compliant
- Solar or AC Powered
- Day or Night Visibility
- White or Yellow LED's

Multiple Activation Options

SPEED LIMIT

ХХ

- Fast Easy Installation
- Mounting Systems Available

(Text) and/or (Graphic)

Pedestrian/Warning LED Signs Solar / AC Powered

Warning Series Model

Specifications

Construction	.080 Highway Grade Aluminum/ Stainless Fasteners
Reflective Sheeting	Type IX Reflective Sheeting Fluorescent Yellow Green Sheeting
Circuitry Technology	Sealed PCB Technology Micro-Controller Circuitry 24 Hour Operation 50 to 60 Times Minute Flash Rate
Solar/AC/Battery Specifications (Depending on Model)	15-20 Watt Polycrystalline Solar Cell 6-12 Volt SLA Battery (2 to 4-year battery life) AC Power (Up to 264 Volts)
LED Lighting	8-G2 LED Lighting in Sign Perimeter Cree High Power Red LED - Max 3.5 Watts Field Replacement Grommet Mounted Lights Reflective LED Lighting (Patented)
Sizes	24" (4 LED's ONLY) / 30" / 36" / 48" / 60"



Day View



Specifications subject to change without notice

Features

- MUTCD Section 2A.07 / 2A.08 Compliant
- FLash Rate 50 to 60 Times Per Minute
- Up to 25 Days of Operation Flashing 24 Hours 7 Days
- LED Life Expectancy over 100,000 Hours
- White / Yellow LED Lights
- Multiple Mounting Hardware Options
- Keyed On / Off Switch
- Easy Battery Replacement in Field
- Quick LED Light Replacement

Warranty 10 Year Solar Collector Panel 5 Year Sign Construction 2 Year PCB/LED Technology 1 Year Battery

Options: Standard & Deluxe Timers / Wireless Activation-Communications **Push Button Activation**

Patent # 7,937,838

Call Toll Free: 877-977-SIGN (7446) •